


# YT07 | Direct-Indirect Aluminum Extrusion

**BEULUX**

YT07 is the base extrusion for a pendant with direct only or direct - indirect light solution. Can be compatible with L90 – L400, RGB, and Tunable White. It is made of anodized aluminum and can be cut on site. To be installed without diffuser or with one out of the YT diffuser range YT99-SL, YT99-CL, YT99-DL.



## Product Detail

- Extrusion: YT07
- Material: Extruded aluminum
- Color: Anodized silver
- Size in Inch: L 78 3/4 x W 1 1/16 x H 1
- Customization: Cut to any length

## Compatibility

- Tapelight: Maximum 400 lm/ft, RGB, TW
- Lens: Clear, drop, Satined lens
- Accessories: Cable suspension, linear connector, end cap
- Connector: Connector, cable, power feed
- Power Supply: Dimming, Non-Dimming

## Compatible Lens



**YT99-SL**  
Satined Lens  
PMMA, 82% transmission




**YT99-DL**  
Satined Drop Lens  
PMMA, 82% transmission



**YT99-CL**  
Clear Lens  
PMMA, 93% transmission


## YT07 Extrusion + Lens

Satined Lens




YT07 +  
YT99-SL

Drop Lens



YT07 +  
YT99-DL

Clear Lens



YT07 +  
YT99-CL

## Compatible Accessories

Suspension



**ZZ99-CS**

Linear  
Connector



**ZZ99-LC**

End Cap



**YT07-EC**

## Tape Light

Output	IP Rating	Color Temp
L90 = 90 lumens/ft L180 = 180 lumens/ft L270 = 270 lumens/ft L400 = 400 lumens/ft	IP00 = Indoor IP66 = Outdoor	CT27 = 2700k CT30 = 3000k CT40 = 4000k
	IP00 = Indoor	CT35 = 3500k
RGB = Color Changing	IP00 = Indoor IP66 = Outdoor	None
TW = Tunable White	IP00 = Indoor IP66 = Outdoor	CT27-40 = 2700k-4000k

## Technical Information

Output	L90	L180	L270	L400	RGB	Tunable White
LEDs/ft	36	36	36	36	18	72
Lumens/ft @ 4000K	90	180	270	400	Max 110	460
Consumption (watt/ft)	0.73	1.62	2.5	3.66	2.2	4.12
Efficacy @ 4000k (lm/watt)	123	111	108	109		111
CRI	>80	>80	>80	>80		>80
Voltage	24	24	24	24	24	24
Maximum run length	75'	52'	35'	30'	20'	30'
Customization increment	2"	2"	2"	2"	4"	2"

## Ordering Code

Extrusion	Lens	Tapelight			Mounting	End Cap
YT07	- SL	- L90	IP00	CT27	- CS	- EC
YT07	SL - Satined Lens DL - Drop Lens CL - Clear Lens	L90 - 90 lm/ft L180 - 180 lm/ft L270 - 270 lm/ft L400 - 400 lm/ft RGB - Color Changing TW - Tunable White	IP00 IP66	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K	CS - Cable Suspension LC - Linear Connector	EC - End Cap

## Power Supply

Model	Power	IP	Input	Output	Dimension (Inch) LxWxH						
TR = Non-Dimming	50 = 50 watt 75 = 75 watt 100 = 100 watt 150 = 150 watt	IP00	88-264V	24V	3.90 X 3.82 X 1.42 5.08 X 3.82 X 1.50 6.26 X 3.82 X 1.50 7.84 X 3.85 X 1.50						
	12 = 12 watt 16 = 16 watt 25 = 25 watt 35 = 35 watt				IP42	90-264V	3.03 X 1.57 X 1.14 3.03 X 1.57 X 1.14 3.31 X 2.24 X 1.16 3.31 X 2.24 X 1.16				
	20 = 20 watt 35 = 35 watt 60 = 60 watt 100 = 100 watt						IP67	90-264V	4.65 X 1.38 X 1.02 5.83 X 1.57 X 1.18 6.40 X 1.67 X 1.26 7.48 X 2.05 X 1.46		
	DTR =Dimming (0-10V)	16 = 16 watt 25 = 25 watt 40 = 40 watt 60 = 60 watt 90 = 90 watt 100 = 100 watt 120 = 120 watt 150 = 150 watt 185 = 185 watt 240 = 240 watt 320= 320 watt 600 = 600 watt	IP67						90-305V	24V	5.83 X 1.57 X 1.26 5.83 X 1.57 X 1.26 6.40 X 1.70 X 1.26 6.40 X 1.70 X 1.26 6.34 X 2.40 X 1.42 8.66 X 2.68 X 1.53 8.66 X 2.68 X 1.53 8.97 X 2.68 X 1.58 8.97 X 2.68 X 1.58 9.88 X 2.68 X 1.58 9.92 X 3.54 X 1.72 11.02 X 5.67 X 1.91
		DTR – FP = Dimming (Forward Phase)			20 = 20 watt 40 = 40 watt 60 = 60 watt 75 = 75 watt 96 = 96 watt	IP67					120V

## Power Supply Ordering Code


Model	Power	IP	Description
TR	50	IP00	Non-Dimming, 50 watt, IP00, 88-264V output, 24V input
DTR	16	IP67	0-10V Dimming, 16 watt, IP67, 90-305V output, 24V input
DTR-FP	20	IP67	Forward Phase-Dimming, 20 watt, IP67, 120V output, 24V

## Customization


Code	Description	Customization
T20-CUST	Tapelight Customizing	Cut tape to exact length (2" increments)
TL20-CUST	Tapelight Customizing + Lead Wires	Cut tape to exact length + solder 4' lead wire
E20-CUST	Extrusion Customizing	Cut tape & extrusion to exact length, installing tape, add strain relief, and solder 4' lead wire
E20-CUST-C	Extrusion Customizing Color	
E20IP68-1-CUST	Extrusion Customizing IP68 for 1-2 feet	
E20IP68-3-CUST	Extrusion Customizing IP68 for 3-4 feet	
E20IP68-5-CUST	Extrusion Customizing IP68 for 5-6 feet	

## Connectors

**CON-S**  
Splice connector





**CON2-JC**  
Jumper Cable with  
2" cable



**CON20-JC**  
Jumper Cable with  
20" cable



**CON20-PF**  
Power feed for white  
tapelight with 20" cable



**CON20RGB-PF**  
Power feed for RGB  
tapelight with 20" cable

