





The CT06 stands out with its dual-purpose design, serving as both a sturdy closet rod and a compact lighting fixture. This unique extrusion is crafted from high-quality anodized aluminum, blending functionality with elegance.

CT06

CT06-CL60
60° Clear Lens

CT06-DL
Drop Lens

CT06-AL
Asymmetric Lens



CT06-EC
End Cap

CT06-ES
End Support

CT06-CS
Center Support



Product Detail

Material:	Extruded Aluminum
Color:	Anodized Silver
Dimension (in):	L 78.74" x W 0.59" x H 1.03"
Customization:	Cut to specified length

Applications

- Closet Rod

Compatible LED Tapelight

Product	Output (~lm/ft)	LEDs/ft	Consump. (watt/ft)	Efficacy (~lm/watt)	CRI	Voltage	Max Run Length	Cut Increment
---------	-----------------	---------	--------------------	---------------------	-----	---------	----------------	---------------

Vienna (High End)

L90	90	36	0.73	123	>80	24	75'	1.97"
L270	270	36	2.7	108	>80	24	34'	1.97"
L400	400	36	3.9	109	>80	24	25'	1.97"
L610	610	36	6.2	104	>80	24	18'	1.97"
Dim-To-Warm	320	51	2.9	109	>80	24V	10'	3.28"

Florence (Mid-Range)

L200	200	36	1.6	125	>90	24	55'	1.97"
L360	360	36	2.9	124	>90	24	42'	1.97"
L500	500	36	4.3	116	>90	24	32'	1.97"
L780	780	36	6.9	113	>90	24	24'	1.97"
RGB	200	36	7.3	29	N/A	24	16'	1.97"
Tunable White	590	73	5.9	100	>90	24	16'	1.97"
Dim-To-Warm	168	73	4.4	38	>90	24V	16'	1.97"

Athens (Economy)

L240	240	36	2.1	117	>90	24	26'	1.97"
L460	460	36	4.1	114	>90	24	16'	1.97"
L680	680	36	6.3	109	>90	24	13'	1.97"

Ordering Code: CT06 + Tapelight + Accessories + Lengths

CT06	- DL	- F	- L200	IP00	CT35	- EC	- MC	- 4'		
Extrusion	Lens	Tapelight				End Cap	Mounting	Length		
CT06	CL60 - 60° Lens	V – Vienna	L90	~90 lm/ft	IP00	CT22	2200K	EC – End Cap	ES – End Support	Enter run length
			L270	~270 lm/ft	IP66	CT27	2700K			
	L400		~400 lm/ft		CT30	3000K				
	L610		~610 lm/ft		CT35	3500K				
					CT40	4000K				
	DL - Drop Lens							CS – Center Support		
	AL - Asymm. Lens		DTW	Dim-To- Warm	IP00	1900-3000K				
			F – Florence	L200	~200 lm/ft	IP00	CT27	2700K		
				L360	~360 lm/ft	IP66	CT30	3000K		
				L500	~500 lm/ft		CT35	3500K		
				L780	~780 lm/ft		CT40	4000K		
			RGB TW	RGB Tunable White	IP00 IP54	N/A				
			DTW	Dim-To- Warm	IP00 IP54	2100-3000K				
		A – Athens	L240	~240 lm/ft	IP00	CT27	2700K			
			L460	~460 lm/ft	IP66	CT30	3000K			
			L680	~680 lm/ft		CT35	3500K			
						CT40	4000K			

Power Supply Ordering Codes

DTR		+	60		+	IP67		DTR60IP67 - Dimming, 60 Watt, IP67													
MODEL		+	POWER		+	IP RATING		INPUT	OUTPUT	DIMENSION											
NTR Non-Dimming		+	50	50 Watt	+	IP00	Indoor	88-264V	24V	3.90 x 3.82 x 1.42											
				75 Watt						5.08 x 3.82 x 1.50											
				100 Watt						6.26 x 3.82 x 1.50											
				150 Watt						7.84 x 3.85 x 1.50											
				200 Watt						8.46 x 4.53 x 1.18											
				320 Watt						8.46 x 4.53 x 1.18											
				750 Watt						9.84 x 5.00 x 1.61											
				960 Watt						11.60 x 5.00 x 1.61											
				12							+	12	12 Watt	+	IP42	Indoor	90-264V	24V	3.03 x 1.57 x 1.14		
													16 Watt						3.03 x 1.57 x 1.14		
													25 Watt						3.31 x 2.24 x 1.16		
													35 Watt						3.31 x 2.24 x 1.16		
20		+	20	20 Watt	+	IP67	Outdoor	90-264V	24V	4.65 x 1.38 x 1.02											
				35 Watt						5.83 x 1.57 x 1.18											
				60 Watt						6.40 x 1.67 x 1.26											
				100 Watt						7.48 x 2.05 x 1.46											
				150 Watt						7.52 x 2.48 x 1.48											
				320 Watt						9.92 x 3.54 x 1.72											
DTR Dimming min 10% (0-10V)		+	16	16 Watt	+	IP30	Indoor	90-305V	24V	5.83 x 1.57 x 1.26											
				25 Watt						+	IP67	Outdoor	90-305V	24V	5.83 x 1.57 x 1.26						
				40 Watt											6.40 x 1.70 x 1.26						
				60 Watt											6.40 x 1.70 x 1.26						
				90 Watt											6.34 x 2.40 x 1.42						
				96 Watt											8.66 x 2.68 x 1.53						
				120 Watt											8.66 x 2.68 x 1.53						
				150 Watt											8.97 x 2.68 x 1.58						
				185 Watt											8.97 x 2.68 x 1.58						
				240 Watt											9.88 x 2.68 x 1.58						
				320 Watt											9.92 x 3.54 x 1.72						
				480 Watt											10.32 x 4.92 x 1.72						
600 Watt	11.02 x 5.67 x 1.91																				
FPD Dimming min 1% (Forward Phase)		+	20	20 Watt	+	IP67	Outdoor	120V	24V	4.92 x 2.20 x 0.79											
				40 Watt						4.92 x 2.20 x 0.79											
				60 Watt						4.92 x 2.20 x 0.79											
				75 Watt						4.92 x 2.20 x 0.79											
				96 Watt						4.92 x 2.20 x 0.79											
				FPD Dimming min 1% (Forward Phase) with junction box							+	20	20 Watt	+	IP67	Outdoor	120V	24V	5.60 x 2.00 x 2.14		
40 Watt	5.60 x 2.00 x 2.14																				
60 Watt	6.62 x 2.58 x 2.33																				
96 Watt	6.62 x 2.58 x 2.33																				
150 Watt	9.80 x 3.00 x 2.74																				
300 Watt	10.07 x 4.20 x 3.50																				

CUSTOMIZATION	TL48	LN99	EX99	M99	C99	F48	F48C	IP68
Cutting tapelight to specified length + solder 4ft leadwire	✓					✓	✓	
Installing tapelight onto extrusion						✓	✓	
Cutting diffuser to specified length		✓				✓	✓	
Cutting extrusion to specified length			✓			✓	✓	
Miter corner extrusion and diffuser				✓				
Filling extrusion with polyurethane (2 ft submersible)								✓
Customize extrusion to specified color					✓		✓	
Final function and quality inspection	✓	✓	✓	✓	✓	✓	✓	✓