


# XT01 | Recessed Extrusion



XT01 is a very common recessed extrusion as it is still quite small but can hold all lumen output tapes of the Beulux range. Made from anodized aluminum it has great heat dissipation capabilities.



## Product Detail:

Material: Extruded Aluminum  
Color: Anodized Silver  
Size in inch: L  $78 \frac{3}{4}$  x W  $29 \frac{3}{32}$  x H  $45 \frac{5}{64}$   
Customization: Cut to specified length


## Applications:

- Recessed with Trim
- Transition Wall/Ceiling
- Hallways
- Millwork
- Vanity
- Office
- Retail

## Compatible Lens


### XT99-CLS

Seamless Clear Lens




### XT99-SLS

Seamless Satined Lens



### XT99-DL

Satined Drop lens



### XT99-CL30

30° Clear Lens



Seamless clear and satined lens are available up to 19' 6" length

## Compatible LED Tapelight

Product	Output (~lm/ft)	LEDs/ft	Consump. (watt/ft)	Efficacy (~lm/watt)	CRI	Voltage	Max Run Length	Cut Increment
---------	-----------------	---------	--------------------	---------------------	-----	---------	----------------	---------------

### Vienna (High End)

L90	90	36	0.73	123	>80	24	75'	2"
L180	180	36	1.62	111	>80	24	47'	2"
L270	270	36	2.7	108	>80	24	34'	2"
L400	400	36	3.9	109	>80	24	25'	2"
L610	610	36	6.2	104	>80	24	18'	2"
L910	910	36	9.7	104	>80	24	10'	2"
RGB	Max 110	18	2.2	N/A	N/A	24	20'	4"
Tunable White	460	72	4.12	111	>80	24	30'	2"

### Florence (Mid-Range)

L200	200	36	1.6	125	>90	24	55'	2"
L360	360	36	2.9	124	>90	24	42'	2"
L500	500	36	4.3	116	>90	24	32'	2"
L780	780	36	6.9	113	>90	24	24'	2"
L990	990	36	9.2	108	>90	24	16'	2"
RGB	200	36	7.3	29	N/A	24	16'	2"
RGBW	330	29	7.3	47	N/A	24	16'	2.5"
Tunable White	590	73	5.9	100	>90	24	16'	2"

### Athens (Economy)

L240	240	36	2.1	117	>90	24	26'	2"
L460	460	36	4.1	114	>90	24	16'	2"
L680	680	36	6.3	109	>90	24	13'	2"

### Paris (MegaCRI 95+)

L500	564	36	6.1	92	>95	24	16'	2"
------	-----	----	-----	----	-----	----	-----	----

### Madrid (120V)

L360	360	22	4	90	>80	120	164'	4"
------	-----	----	---	----	-----	-----	------	----

## Ordering Code Template: XT01 + Tapelight + Accessories


Extrusion	Lens	TL Line	Lumen Output	IP	CCT	End Cap	Mounting
-----------	------	---------	--------------	----	-----	---------	----------

## Ordering Code: XT01 + Tapelight + Accessories

XT01	- DL	- F	- L200	IP00	CT35	- EC	- RS
------	------	-----	--------	------	------	------	------

Extrusion	Lens	Tapelight			End Cap	Mounting	
XT01	CL – Clear Lens SLS – Seamless Satined Lens DL - Drop Lens CL35 – 35° Clear Lens	V – Vienna	L90 – 90 lm/ft L180 – 180 lm/ft L270 – 270 lm/ft L400 – 400 lm/ft L610 – 610 lm/ft L910 – 910 lm/ft RGB - RGB TW - Tunable White	IP00  IP66	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K  CT27 - 2700K CT30 - 3000K CT40 - 4000K	EC – End Cap ECD – End Cap for Drop Lens	MC – Mounting Clip RS – Recess Spring AA – Adj. Angle AA90 – 90° Adj. Angle
		F – Florence	L200 – 200 lm/ft L360 – 360 lm/ft L500 – 500 lm/ft L780 – 780 lm/ft L990 – 990 lm/ft  RGB - RGB RGBW - RGBW TW - Tunable White	IP00 IP66	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K  N/A		
		A – Athens	L240 – 240 lm/ft L460 – 460 lm/ft L680 – 680 lm/ft	IP00 IP66	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K		
		P – Paris	L500 – 564 lm/ft	IP20	CT24 - 2400K CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K		
		M – Madrid	L360 – 360 lm/ft	IP65	CT27 - 2700K CT30 - 3000K CT35 - 3500K CT40 - 4000K		

## Accessories



## Connectors *(applicable with Florence and Vienna)*



Customization	LN20-CUST	EX20-CUST	M20-CUST	E20-CUST	E20-CUST-C	E20IP66-CUST	E20IP68-1-CUST	E20IP68-2-CUST	E20IP68-3-CUST
Cutting lens to specified length	✓								
Cutting extrusion to specified length		✓							
Miter corner extrusion and diffuser			✓						
Cutting extrusion, diffuser, and tapelight				✓	✓	✓			
Cutting extrusion, diffuser, and tapelight to 1-2 ft							✓		
Cutting extrusion, diffuser, and tapelight to 3-4 ft								✓	
Cutting extrusion, diffuser, and tapelight to 5-6 ft									✓
Installing the tapelight into the extrusion				✓	✓	✓	✓	✓	✓
Adding strain relief and power feed				✓	✓		✓	✓	✓
Adding strain relief and power feed w/ heat sink tube						✓			
Mounting end caps				✓	✓	✓			
Mounting and sealing end caps							✓	✓	✓
Customize to specified color					✓				
Solder 4 ft lead wire				✓	✓	✓	✓	✓	✓
Filling extrusion w/ clear material => 2 ft submersible							✓	✓	✓
Final function and quality inspection	✓	✓	✓	✓	✓	✓	✓	✓	✓

## Power Supply Ordering Code

TR + 50 + IP00 = Non-Dimming, 50 watt, IP00, 88-264V output, 24V

1 - Model	2 - Power	3 - IP	Input	Output	Dimension (Inch) LxWxH
<b>TR = Non-Dimming</b>	50 = 50 watt 75 = 75 watt 100 = 100 watt 150 = 150 watt	<b>IP00</b> = Indoor	88-264V	24V	3.90 X 3.82 X 1.42 5.08 X 3.82 X 1.50 6.26 X 3.82 X 1.50 7.84 X 3.85 X 1.50
	12 = 12 watt 16 = 16 watt 25 = 25 watt 35 = 35 watt	<b>IP42</b> = Indoor	90-264V		3.03 X 1.57 X 1.14 3.03 X 1.57 X 1.14 3.31 X 2.24 X 1.16 3.31 X 2.24 X 1.16
	20 = 20 watt 35 = 35 watt 60 = 60 watt 100 = 100 watt	<b>IP67</b> = Outdoor	90-264V		4.65 X 1.38 X 1.02 5.83 X 1.57 X 1.18 6.40 X 1.67 X 1.26 7.48 X 2.05 X 1.46
<b>DTR = Dimming (0-10V)</b>	16 = 16 watt 25 = 25 watt 40 = 40 watt 60 = 60 watt 90 = 90 watt 100 = 100 watt 120 = 120 watt 150 = 150 watt 185 = 185 watt 240 = 240 watt 320 = 320 watt 600 = 600 watt	<b>IP67</b> = Outdoor	90-305V	24V	5.83 X 1.57 X 1.26 5.83 X 1.57 X 1.26 6.40 X 1.70 X 1.26 6.40 X 1.70 X 1.26 6.34 X 2.40 X 1.42 8.66 X 2.68 X 1.53 8.66 X 2.68 X 1.53 8.97 X 2.68 X 1.58 8.97 X 2.68 X 1.58 9.88 X 2.68 X 1.58 9.92 X 3.54 X 1.72 11.02 X 5.67 X 1.91
<b>DTR – FP = Dimming (Forward Phase)</b>	20 = 20 watt 40 = 40 watt 60 = 60 watt 75 = 75 watt 96 = 96 watt	<b>IP67</b> = Outdoor	120V	24V	4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77 4.92 X 1.97 X 0.77